## **Product Data Sheet** Lyra 130 LED Projector



No Driver Required

## Collezione Italiana







Hood




Mounting Spike

	Code	Lamp	Description
Projector	ALYLED12/PR/GR	LED 240V	12W Cool White (12° Beam) - Graphite
	ALYLED40/PR/GR	LED 240V	12W Cool White (40° Beam) - Graphite
	ALYLED12/PR/SI	LED 240V	12W Cool White (12° Beam) - Silver
	ALYLED40/PR/SI	LED 240V	12W Cool White (40° Beam) - Silver
Accessories	ALYLEDHOOD/GR	Hood - Graphite	
	ALYLEDHOOD/SI	Hood - Silver	
	ALYLEDSPIKE	Mounting Spike	
	AWC/1	Wire Cage W330 x D435 x H410mm	

## www.anselluk.com

- Architectural LED surface projector
- Powered by 240V 12W Acriche Seoul LED's (6000°k) nominal lumen 78oLM
- Direct mains connection (no driver is required)
- 350 degree rotation, adjustable 45 degree downward angle and 90 degree upwards angle
- Aluminium construction with clear tempered glass
- See wire cage accessories

















## **Product Data Sheet** Lyra 130 LED Projector



No Driver Required



	Code	Lamp	Description
Extension Arm	ALYLED12/EAPR/GR	LED 240V	12W Cool White (12° Beam) - Graphite
Projector	ALYLED40/EAPR/GR	LED 240V	12W Cool White (40° Beam) - Graphite
	ALYLED12/EAPR/SI	LED 240V	12W Cool White (12° Beam) - Silver
	ALYLED40/EAPR/SI	LED 240V	12W Cool White (40° Beam) - Silver
Accessories	ALYLEDHOOD/GR	Hood - Graphite	
	ALVI EDHOOD/CI	Hood Cilvor	

Accessories	ALYLEDHOOD/GR	Hood - Graphite
	ALYLEDHOOD/SI	Hood - Silver
	ALYLEDSPIKE	Mounting Spike
	AWC/1	Wire Cage W330 x D435 x H410mm

www.anselluk.com

- Architectural LED surface projector
- Powered by 240V 12W Acriche Seoul LED's (6000°k) nominal lumen 78oLM
- Direct mains connection (no driver is required)
- 350 degree rotation, adjustable 45 degree downward angle and 90 degree upwards angle
- Aluminium construction with clear tempered glass
- See wire cage accessories

